


# Wireless DMX

Leprecon has gone wireless! With the help from our friends at Wireless Solutions in Sweden, our ULD series dimmers can now receive DMX-512 wirelessly. We've combined the industry leaders in tree-mount dimming and wireless DMX to bring you a portable dimmer with more features and reliability than anything on the market.



The W-DMX™ series transmitter and receiver use adaptive frequency hopping technology to continually check for interference and to rapidly scan and move signal to clear radio channels. This ensures smooth, efficient and robust operation. In fact, W-DMX™ gives you greater freedom to create reliable wireless point-to-point, point-to-multi point and multi point-to-multi point installations over large distances.

## FEATURING:

- Range: up to 2300 feet indoors w/ 2dBi antenna
- Adaptive Frequency Hopping Spread Spectrum (AFHSS) – 2.45 GHz
- Run up to 16 DMX-512 universes in one system
- Plug and Play Operation


**Wireless DMX** is an optional add-on package to the Leprecon ULD and LDS series dimmers. With the wireless receiver built-in to the ULD or LDS dimmers, users can now conveniently and reliably control up to 512 channels of DMX.

### Receiver

Built into Leprecon ULD and LDS series dimmers, the receiver comes standard with 2dBi antenna, an LED indicator for Power and DMX presence. Non-volatile memory holds settings for power level and hopping pattern in the event there is a loss of power.

Part Number	Description
90-06-0280	ULD-340, SP, Duplex, 4 Ch, ETL
90-06-0281	ULD-340, HP, Duplex, 4 Ch, ETL
90-06-0286	ULD-360, HP, Stage Pin, 6 Ch, ETL
90-06-0287	ULD-360, HP, Duplex, 6 Ch, ETL
90-06-0285	ULD-360, 20A, HP, Duplex, 6 Ch
27-0046	R-512 Stand Alone Receiver

Wireless DMX available in LDS series models.  
Call for details.



### S-1 Micro Transmitter

Has an internal 2dBi antenna for up to 1600 feet in line of sight from console, built-in battery backup for up to 8 hours and one button technology to view signal quality and battery power. LED indicators: Power, Assigned, RF Link and DMX-512. Power with 12VDC via RJ45 connector.

### S-1 Standard Transmitter

Includes an external 2dBi antenna for up to 2300 feet in line of sight from console, one button technology for search and link to receivers and LED indicators for Power, Assigned, RF Link and DMX-512. Power with 120VAC power cord, 12VDC, or via DMX bypass (RJ45).



Part Number	Description
27-0039	S-1 Transmitter
27-0038	S-1 Micro Transmitter
27-0045	S-2 Transmitter, 2 Universe
27-0035	2dBi antenna, replacement
27-0044	5dBi antenna

One Year Warranty on Transmitter

Full Two Year Warranty on Dimmers with Built-in W-DMX™ Receiver.  
Contact dealer for details.

