



Inline Hoist

Applications

- For use in schools, auditoriums, professional theatres and worship facilities providing safe and convenient set and scenery movement.

Dependable

- Dual motors, dual gearboxes and dual brakes to ensure reliable stops and secure holds for long periods.
- A single, solid shaft connects dual motors, dual brakes and drum for redundant operation.
- Redundant limit switches and emergency stop functions.
- Starters and drives are U.L. listed.



Features

- A range of speeds and lifting capacities are available, with fixed or variable speed operation.
- Configurations are available with 3/16" to 1/4" cables to meet your lift requirements. No need to settle for standard off the shelf configurations.
- Horizontal or vertical mounting to meet your system layout.

Control Systems

- Manual pushbutton back up provided on all systems.
- Texas Scenic Company's Deck Boss® Control System console.
- Slack line and load monitoring (optional) to work with the Deck Boss® Control System and other high-end control systems.
- Other control options available.

Specifications

Speed	15 to 60 fpm fixed speed, 0 to 180 fpm variable, custom speeds available.
Weight	1200 pound and 1800 pound standard capacities.
Lift Lines	Available in four, five, six, seven and eight configurations.
Height	Travel up to 65 ft. standard, other travel heights available.
Power Requirements	3 Phase, 208 volt or 460 volt power requirements.