

PIONEER II

FEATURES

- Fixed and variable speed control for up to 100 axes.
- Easy operation with 2 access modes:
 - Basic Push button limit to limit moves. Targeted movement. Prerecorded preset movement
 - Advanced Basic functionality plus saving capability and axis detail editing
- Multi hoist operation
- Ability to move multiple hoists in opposing directions
- User editable hoist tile screen names
- Hoist status, position, target, and load (when applicable)
- Advanced user axis preset saving (6 per hoist)
- Emergency stop button
- Hold to run operation through provided "GO" button
- Maximum selected hoist limitation to reduce mechanical and electrical load as needed
- Simple show cuing (when applicable)

APPLICATIONS

- Stage rigging controller for fixed and variable speed speed hoists
- FOH motorized truss lighting systems
- Banners and curtains
- Speaker systems

ACCESSORIES

- Remote "GO" pendant with integrated emergency stop
- Remote touch pendant with HTR and emergency stop
- Up to 10 emergency stop stations
- Flush and Rack mountable options

SPECIFICATIONS

- Mechanical
 - Industrial steel back box with engraved anodized aluminum front panel
 - 6" back box depth
 - 16" back box width
 - 16" box height, plus mounting tabs
- Electrical
 - Termination on terminals and connectors
 - Hardwired hold to run circuit
 - Emergency stop circuit
 - 24VDC low voltage operation
 - Industrial ethernet network
 - UL508A certified
- Electronics
 - Full color 12" touch panel interface
 - Industrial grade, Go push button and illuminated emergency stop button
 - System power key switch (maintained)
 - Optional remote-control receptacle

